

POSMO

POSMO is a compact touchscreen monitor featuring the same modern and a compact body with a small footprint to save valuable counter space. Industrial-grade LED, LCD panel offers bright and crisp image, extended product life And energy efficiency. Its stable base stand, adjustable viewing angle and integrated MSR/IC reader make it a versatile solution for Point-of-Sale or Point-of-Information environments. It can be placed on a counter or wall mounted.



POSMO System

	POSMO III-2150	POSMO III-1500
Display		
Size	21.5" TFT LCD, LED Backlight	15" TFT LCD, LED Backlight
Resolution	1920 x 1080	1024 x 768 Resolution
Brightness	300 cd/m ² (typ.)	300cd/m ² (typ.)
Contrast Ratio	1,000:1	500:1
View Angle (U/D/R/L)	89° / 89° / 89° / 89°	80° / 80° / 80° / 80° (typ.)
Touchscreen		
Type	Projected Capacitive Touch	
Controller Interface	USB Interface	
Interface		
VGA	1 x VGA	
HDMI	1 x HDMI (Factory Option)	
USB (A Type)	4 x USB 2.0	
USB (B Type)	1 x USB 2.0	
MSR	1 (RJ-45 for MSR, SCR, i-button)	
Audio	1 x Line-out	
Power		
Power Supply	Adapter 12V, 5A	
Physical & Environmental		
Dimensions (W x H x D)	490 x 337 x 210 (mm), 19.3 x 13.3 x 8.2 (in)	364 x 333 x 210 (mm), 14.3 x 13.1 x 8.2 (in)
Net Weight	6,200g, 13.7lbs	4,800g, 10.6lbs
Packing Dimensions (W x H x D)	640 x 465 x 300 (mm), 25.2 x 18.3 x 11.8 (in)	500 x 470 x 300 (mm), 19.6 x 18.5 x 11.8 (in)
Packing Weight	9,100g, 20.1lbs	7,500g, 16.5lbs
Certification	CE, FCC, KC	CE, FCC, KC
Options and Peripherals		
Wall Mount Kit	VESA-Compatible, 75 x 75 (mm), 100 x 100 (mm)	
Speaker	2 x 1W (Stereo) (Factory Option)	
Multi-Reader	MSR : Comply with ISO 7811, Support 16 2 & 3 Track SCR : EMV Level 1 Dallas : i-button Reader	

* Specifications may change without prior notice.